


# IP Outdoor Station

## 280D-B9

Comparing with 902 Android intercom system, 280 Linux intercom system is more cost-effective. It offers multiple functions, including video intercom, door access, emergency call, security alarm, and property management, etc. It also supports communication with IP phone or SIP softphone, etc. via SIP protocol, and can be used with home automation and lift control system.




### Specifications:

Physical Property	
System	Linux
CPU	1GHz, ARM Cortex-A7
SDRAM	64MB DDR2 SDRAM
FLASH	128MB NAND FLASH
Screen	4.3 inch LCD,480x272
Power	DC 12V/PoE
Standby power	1.5W
Rated Power	9W
Card Reader	IC/ID(Optional) Card, 20,000 pcs
Button	Mechanical Button/Touch Button(optional)
Temperature	-40 - +70
Humidity	20%-93%
IP Class	IP65
Installation	Flush Mounted
Audio & Video	
Audio Codec	G.711
Video Codec	H.264
Camera	CMOS 2M pixel
Video Resolution	1280x720p
LED Night Vision	Yes
Network	
Ethernet	10M/100Mbps, RJ-45
Protocol	TCP/IP, SIP
Interface	
Unlock circuit	Yes(maximum 3.5A current)
Exit Button	Yes
RS485	Yes
Door Magnetic	Yes


### Key features:

- Open the door by IC/ID card (20,000 users)
- Elevator control
- Standard SIP 2.0
- PoE

### Dimension & Installation:



Product Size	158x380x55.7mm
Built-in box size	142x358x59.5mm
Installation size	148x364x65mm



- ① Outdoor panel
- ② Screw
- ③ Built-in box

IN COLLABORATION WITH

**TECHRAQ** | **DNAKE**

TECHRAQ Trading W.L.L.P.O.Box: 16926, CR. 174362 , 203B Block,Gold Tower, Khalidiya Street, Doha , Qatar  
 T +97 4 5031 5682 E sales@sltechraq.com www.sltechraq.com