

Datasheet

Instruction

The DNAKE 902C-A is mainly used in guard station, it enables concierge to send messages, for example utilities, weather forecast, etc. to apartment residents. It can also manage the access control for visitors, to gives you the combined benefit of security and convenience.

DNAKE 902C -A



Key Features

- 10.1-inch capacitive touch screen
- Android System
- Alarm/Call logs
- Message Sending/Receiving
- Powered by PoE or power adapter (DC12V/2A)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Support monitoring 8 IP cameras

Physical

- System: Android
- RAM: 512 MB
- ROM: 4 GB
- Front Panel: Plastic
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 3 W
- Rated Power: 10 W
- Camera: 0.3MP, CMOS
- SD Card Port: 1
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Installation: Desktop
- Dimension: 303 x 195 x 35 mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

Datasheet

Display

- Display: 10.1-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Video

- Video Codec: H.264

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Package Features

- Package Content:
 - DNAKE 902C-A
(Power adapter not included)
 - Screwing Kit
 - Quick Start Guide
- Qty/CTN: 8 pcs
- N.W/PCS: 1.29 kg
- G.W/CTN: 14.64 kg
- Giftbox Size: 350 x 336 x 80 mm
- Carton Size: 360 x 640 x 460 mm

IN COLLABORATION WITH

TECHRAQ[™]

DNAKE

TECHRAQ Trading W.LLP.O.Box: 16926, CR. 174362, 203B Block, Gold Tower, Khalidiya Street, Doha, Qatar

T +97 4 5031 5682 E sales@stechraq.com www.stechraq.com